

KYTOLA® Alarm Amplifier Model NK is designed for use with inductive proximity sensors according to NAMUR norm (EN 60947).

The alarm amplifier has a common relay output, and it is activated if one or more sensors connected to it alarm.



- Function indicator LEDs on the enclosure cover
- Common group alarm
- Inputs for 1 – 30 NAMUR sensors, depending upon model

ALARM AMPLIFIER NK

FEATURES

Protection class IP 54

Potential free change-over switch

TYPICAL APPLICATIONS

Indication of low flow alarm in oil lubrication systems

Indication of low or high flow alarm in sealing and cooling water systems

Gas flow alarm

Supply voltage	24 VDC, 110 VAC, or 220 VAC depending on model		
Inputs	For sensors according to NAMUR norm (EN 60947)		
Output	One common potential-free NO/NC change-over switch, 230 VAC, 5 A		
Protection class	IP54		
Function indicator LEDs	Green: System OK (no alarms) Red: Alarm (one or more sensors alarm)		
Dimensions (H x L x W)	NK-2	130 x 130 x 75 mm	
	NK-12	180 x 180 x 75 mm	
	NK-30	180 x 255 x 75 mm	

NK- /

Inputs for x sensors (2, 12 or 30)	x
Supply voltage	
24 VDC	24
110 VAC	110
220 VAC	220

